

	Units	DT 4.10	
		50Hz	60Hz
Flow	m ³ /h	10	12
Overpressure,max	bar	1	
Motor power	kw	0.37	0.44
R.P.M.		1420	1740
Single phase motor , volts		230V+-10%	
Three phase motor, volts		175-260/300-450V	202-300/350-520V
Noise level, dB(A), 1 meter		60	
Length	mm	429	
Width	mm	206	
Height	mm	195	
Inter port thread	G”	1/2”	
Weight with motor	kg	16	

	Units	DT 4.16	
		50Hz	60Hz
Flow	m ³ /h	16	19.2
Overpressure,max	bar	1	
Motor power	kw	0.55	0.66
R.P.M.		1420	1740
Single phase motor , volts		230V+-10%	
Three phase motor, volts		175-260/300-450V	202-300/350-520V
Noise level, dB(A), 1 meter		62	
Length	mm	452	
Width	mm	231	
Height	mm	211	
Inter port thread	G”	1/2”	
Weight with motor	kg	23.5	

	Units	DT 4.25	
		50Hz	60Hz
Flow	m ³ /h	25	30
Overpressure,max	bar	1	
Motor power	kw	1.1	1.3
R.P.M.		1420	1740
Single phase motor , volts		230V+-10%	
Three phase motor, volts		190-255/330-440V	190-290/330-500V
Noise level, dB(A), 1 meter		65	
Length	mm	545	
Width	mm	328	
Height	mm	290	
Inter port thread	G”	3/4”	
Weight with motor	kg	36.5	

	Units	DT 4.40	
		50Hz	60Hz
Flow	m ³ /h	40	48
Overpressure,max	bar	1	
Motor power	kw	1.85	2.2
R.P.M.		1420	1740
Single phase motor , volts		230V+-10%	
Three phase motor, volts		190-255/330-440V	190-290/330-500V
Noise level, dB(A), 1 meter		67	
Length	mm	625	
Width	mm	328	
Height	mm	290	
Inter port thread	G”	3/4”	
Weight with motor	kg	46	