

	Units	DVT3.60	
		50Hz	60Hz
Flow	m ³ /h	58	72
Max. overpressure	+bar	0.6	
Max. negative pressure	-bar	0.6	
Motor power	kw	2.4	3.0
R.P.M.		1420	1740
Three phase motor, volts		230/400V+-10%	
Noise level, dB(A), 1 meter		75	
Length	mm	703	
Width	mm	353	
Height	mm	328	
Inter port thread	G”	1”	
Weight with motor	kg	69	
Weight without motor	kg	47	

	Units	DVT3.80	
		50Hz	60Hz
Flow	m ³ /h	70	96
Max. overpressure	+bar	0.6	
Max. negative pressure	-bar	0.6	
Motor power	kw	4.0	4.8
R.P.M.		1420	1740
Three phase motor, volts		230/400V+-10%	
Noise level, dB(A), 1 meter		75	
Length	mm	703	
Width	mm	353	
Height	mm	328	
Inter port thread	G”	1”	
Weight with motor	kg	72	
Weight without motor	kg	49	

	Units	DVT3.100	
		50Hz	60Hz
Flow	m ³ /h	103	120
Max. overpressure	+bar	0.6	
Max. negative pressure	-bar	0.6	
Motor power	kw	5.5	6.4
R.P.M.		1420	1740
Three phase motor, volts		400/690V+-10%	
Noise level, dB(A), 1 meter		77	
Length	mm	891	
Width	mm	470	
Height	mm	336	
Inter port thread	G”	1 1/2”	
Weight with motor	kg	120	
Weight without motor	kg	71	

	Units	DVT3.140	
		50Hz	60Hz
Flow	m ³ /h	137	168
Max. overpressure	+bar	0.6	
Max. negative pressure	-bar	0.6	
Motor power	kw	7.8	9.3
R.P.M.		1420	1740
Three phase motor, volts		400/690V+-10%	
Noise level, dB(A), 1 meter		78	
Length	mm	929	
Width	mm	470	
Height	mm	336	
Inter port thread	G”	1 1/2”	
Weight with motor	kg	136	
Weight without motor	kg	78	

	Units	DVTLF 250	
		50Hz	60Hz
Flow	m ³ /h	250	300
Max. overpressure	+bar	0.5	
Max. negative pressure	-bar	0.5	
Motor power	kw	7.5	9
R.P.M.		960	1120
Three phase motor, volts		400/690V+-10%	
Noise level, dB(A), 1 meter		83	
Length	mm	1189	
Width	mm	612	
Height	mm	534	
Inter port thread	G”	2 1/2”	
Weight with motor	kg	350	
Weight without motor	kg	235	