

GLD-136A

		Unit	50Hz	60Hz
Actual Pumping Speed		L/min.	135	162
Ultimate pressure		Pa	6.7 x 10 ⁻² (G.V.closed) 6.7 (G.V.open)	
Suction pipe diameter		mm	KF-25	
Weight		kg	24	
Overall dimensions		W x L x H (mm)	170 x 488 x 240	
Motor	Wattage	W	400	
	Selectable Voltage	V	single phase 200-240, 380-460	

GLD-136C

		Unit	50Hz	60Hz
Actual Pumping Speed		L/min.	135	162
Ultimate pressure		Pa	6.7 x 10 ⁻² (G.V.closed) 6.7 (G.V.open)	
Suction pipe diameter		mm	KF-25	
Weight		kg	26	
Overall dimensions		W x L x H (mm)	170 x 488 x 250	
Motor	Wattage	W	400	
	Selectable Voltage	V	Three phase 100-120, 200-240	

GLD-201A

		Unit	50Hz	60Hz
Actual Pumping Speed		L/min.	200	240
Ultimate pressure		Pa	6.7 x 10 ⁻² (G.V.closed) 6.7 (G.V.open)	
Suction pipe diameter		mm	KF-25	
Weight		kg	28	
Overall dimensions		W x L x H (mm)	170 x 516 x 240	
Motor	Wattage	W	550	
	Selectable Voltage	V	Three phase 200-240, 380-460	

GLD-201B

		Unit	50Hz	60Hz
Actual Pumping Speed		L/min.	200	240
Ultimate pressure		Pa	6.7 x 10 ⁻² (G.V.closed) 6.7 (G.V.open)	
Suction pipe diameter		mm	KF-25	
Weight		kg	28	
Overall dimensions		W x L x H (mm)	170 x 516 x 250	
Motor	Wattage	W	550	
	Selectable Voltage	V	Three phase 100-120, 200-240	