

	Units	<b>KDT3.60</b>	
		50Hz	60Hz
Flow	m <sup>3</sup> /h	54	72
Overpressure max.	bar	1.5	
Motor power	kw	2.4	3.0
R.P.M.		1450	1740
Three phase motor, volts		230/400+-10%	
Noise level, dB(A), 1 meter		72	
Length	mm	703	
Width	mm	353	
Height	mm	328	
Inter port thread	G”	1”	
Weight with motor	kg	69	
Weight without motor	kg	47	

	Units	<b>KDT3.80</b>	
		50Hz	60Hz
Flow	m <sup>3</sup> /h	66	96
Overpressure max.	bar	1.5	
Motor power	kw	2.4	3.0
R.P.M.		1450	1740
Three phase motor, volts		230/400+-10%	
Noise level, dB(A), 1 meter		74	
Length	mm	703	
Width	mm	353	
Height	mm	328	
Inter port thread	G”	1”	
Weight with motor	kg	77	
Weight without motor	kg	49	

	Units	KDT3.100	
		50Hz	60Hz
Flow	m <sup>3</sup> /h	99	120
Overpressure max.	bar	1.5	
Motor power	kw	4.0	4.8
R.P.M.		1450	1740
Three phase motor, volts		400/690+-10%	
Noise level, dB(A), 1 meter		76	
Length	mm	891	
Width	mm	470	
Height	mm	336	
Inter port thread	G”	1 1/2”	
Weight with motor	kg	127	
Weight without motor	kg	71	

	Units	KDT3.140	
		50Hz	60Hz
Flow	m <sup>3</sup> /h	129	168
Overpressure max.	bar	1.5	
Motor power	kw	7.5	9
R.P.M.		1450	1740
Three phase motor, volts		400/690+-10%	
Noise level, dB(A), 1 meter		82	
Length	mm	929	
Width	mm	470	
Height	mm	336	
Inter port thread	G”	1 1/2”	
Weight with motor	kg	146	
Weight without motor	kg	78	