

|                             | Units             | <b>T4.16DV</b>   |                  |
|-----------------------------|-------------------|------------------|------------------|
|                             |                   | 50Hz             | 60Hz             |
| Flow                        | m <sup>3</sup> /h | 16               | 19.2             |
| Max. overpressure           | +bar              | 0.5              |                  |
| Max. negative pressure      | -bar              | 0.5              |                  |
| Motor power                 | kw                | 0.55             | 0.65             |
| R.P.M.                      |                   | 1420             | 1740             |
| Single phase motor , volts  |                   | 230V+-10%        |                  |
| Three phase motor, volts    |                   | 175-260/300-450V | 202-300/350-520V |
| Noise level, dB(A), 1 meter |                   | 65               |                  |
| Length                      | mm                | 452              |                  |
| Width                       | mm                | 231              |                  |
| Height                      | mm                | 211              |                  |
| Inter port thread           | G”                | 1/2”             |                  |
| Weight with motor           | kg                | 23.5             |                  |

|                             | Units             | <b>T4.25DSK</b>  |                  |
|-----------------------------|-------------------|------------------|------------------|
|                             |                   | 50Hz             | 60Hz             |
| Flow                        | m <sup>3</sup> /h | 25               | 30               |
| Max. overpressure           | +bar              | 0.6              |                  |
| Max. negative pressure      | -bar              | 0.6              |                  |
| Motor power                 | kw                | 1.1              | 1.3              |
| R.P.M.                      |                   | 1420             | 1740             |
| Single phase motor , volts  |                   | 230V+-10%        |                  |
| Three phase motor, volts    |                   | 190-255/330-440V | 190-290/330-500V |
| Noise level, dB(A), 1 meter |                   | 69               |                  |
| Length                      | mm                | 545              |                  |
| Width                       | mm                | 328              |                  |
| Height                      | mm                | 290              |                  |
| Inter port thread           | G”                | 3/4”             |                  |
| Weight with motor           | kg                | 35               |                  |

|                             | Units             | T4.40DSK         |                  |
|-----------------------------|-------------------|------------------|------------------|
|                             |                   | 50Hz             | 60Hz             |
| Flow                        | m <sup>3</sup> /h | 35               | 48               |
| Max. overpressure           | +bar              | 0.6              |                  |
| Max. negative pressure      | -bar              | 0.6              |                  |
| Motor power                 | kw                | 1.85             | 2.2              |
| R.P.M.                      |                   | 1420             | 1740             |
| Single phase motor , volts  |                   | 230V+-10%        |                  |
| Three phase motor, volts    |                   | 175-260/300-450V | 202-300/350-520V |
| Noise level, dB(A), 1 meter |                   | 68               |                  |
| Length                      | mm                | 625              |                  |
| Width                       | mm                | 328              |                  |
| Height                      | mm                | 290              |                  |
| Inter port thread           | G”                | 3/4”             |                  |
| Weight with motor           | kg                | 46               |                  |