

	Units	U 3.6 SA	
		50Hz	60Hz
Flow	m ³ /h	6.5	7.8
Ultimate vacuum , absolute	mbar	3	
Motor power	kw	0.25	0.3
R.P.M.		1420	1740
Single phase motor , volts		230V+-10%	
Three phase motor, volts		175-260/300-450V	202-300/350-520V
Noise level, dB(A), 1 meter		48	
Length	mm	342	
Width	mm	187	
Height	mm	174	
Inter port thread	G”	3/4”	
Weight with motor	kg	14	

	Units	U 1.16 SA	
		50Hz	60Hz
Flow	m ³ /h	16	19.2
Ultimate vacuum , absolute	mbar	3	
Motor power	kw	0.55	0.66
R.P.M.		1380	1740
Single phase motor , volts		230V+-10%	
Three phase motor, volts		175-260/300-450V	202-300/350-520V
Noise level, dB(A), 1 meter		56.5	
Length	mm	332	
Width	mm	287	
Height	mm	214	
Inter port thread	G”	1/2”	
Weight with motor	kg	24	

	Units	U 4.20	
		50Hz	60Hz
Flow	m ³ /h	18	24
Ultimate vacuum , absolute	mbar	0.5	
Motor power	kw	0.55	0.66
R.P.M.		2880	3400
Single phase motor , volts		230V+-10%	
Three phase motor, volts		175-260/300-450V	202-300/350-520V
Noise level, dB(A), 1 meter		63	
Length	mm	338	
Width	mm	245	
Height	mm	219	
Inter port thread	G”	1/2”	
Weight with motor	kg	20	

	Units	U 3.40 SA	
		50Hz	60Hz
Flow	m ³ /h	40	48
Ultimate vacuum , absolute	mbar	3	
Motor power	kw	1.1	1.3
R.P.M.		1420	1750
Three phase motor, volts		175-260/300-450V	190-290/330-500V
Noise level, dB(A), 1 meter		63	
Length	mm	581	
Width	mm	333	
Height	mm	219	
Inter port thread	G”	1”	
Weight with motor	kg	49	

	Units	U 4.40	
		50Hz	60Hz
Flow	m ³ /h	41	48
Ultimate vacuum , absolute	mbar	0.5	
Motor power	kw	1.5	1.8
R.P.M.		2880	3400
Three phase motor, volts		230/400V+-10%	
Noise level, dB(A), 1 meter		69	
Length	mm	461	
Width	mm	268	
Height	mm	258	
Inter port thread	G”	1”	
Weight with motor	kg	38	